


DEVICE AND METHOD FOR THREE-DIMENSIONAL DISPLAY OF IMAGES**Patent number:** WO03027755**Publication date:** 2003-04-03**Inventor:** WENGER KLAUS HERBERT GUNTER (NL)**Applicant:** DSV GMBH (CH); WENGER KLAUS HERBERT GUNTER (NL)**Classification:****- international:** (IPC1-7): G02B27/22**- european:** G02B27/22P; G02B27/22T**Application number:** WO2002NL00629 20020927**Priority number(s):** NL20011019058 20010928**Also published as:**EP1430352 (A1)
US2005001788 (A)
EP1430352 (B1)
NL1019058C (C2)**Cited documents:**WO9817067
WO0104665
US5083199**Report a data error he****Abstract of WO03027755**

What is disclosed is an image display system comprising an image display device and optical means present at least in front of the viewer, which have a relief structure comprising optical pyramid-shaped elements for suggesting depth in images being viewed by distinguishing between incident light on the left-hand eye and incident light on the right-hand eye of the viewer. Several pyramid-shaped elements are incorporated in the relief structure for each pixel of which the images are built up, as a result of which the alignment of the pixels on the pyramids of the elements will be less critical and, in addition, the occurrence of Moiré distortion in the image is prevented.



Data supplied from the esp@cenet database - Worldwide

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
3 April 2003 (03.04.2003)

PCT

(10) International Publication Number
WO 03/027755 A1

(51) International Patent Classification⁷: **G02B 27/22**

(21) International Application Number: PCT/NL02/00629

(22) International Filing Date:
27 September 2002 (27.09.2002)

(25) Filing Language: Dutch

(26) Publication Language: English

(30) Priority Data:
1019058 28 September 2001 (28.09.2001) NL

(71) Applicant (*for all designated States except US*): **DSV GMBH** [CH/CH]; Aegenstrasse 66, CH-6300 Zug (CH).

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): **WENGER, Klaus, Herbert, Gunter** [NL/NL]; Zebraspoor 573, NL-3605 HH Maarssen (NL).

(74) Agent: **HOOIVELD, Arjen, Jan, Winfried**; Arnold & Siedsma, Sweelinckplein 1, NL-2517 EN The Haag (NL).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DEVICE AND METHOD FOR THREE-DIMENSIONAL DISPLAY OF IMAGES



(57) Abstract: What is disclosed is an image display system comprising an image display device and optical means present at least in front of the viewer, which have a relief structure comprising optical pyramid-shaped elements for suggesting depth in images being viewed by distinguishing between incident light on the left-hand eye and incident light on the right-hand eye of the viewer. Several pyramid-shaped elements are incorporated in the relief structure for each pixel of which the images are built up, as a result of which the alignment of the pixels on the pyramids of the elements will be less critical and, in addition, the occurrence of Moiré distortion in the image is prevented.

WO 03/027755 A1

DEVICE AND METHOD FOR THREE-DIMENSIONAL DISPLAY OF IMAGES

5 The present invention relates to an image display system comprising an image display device and optical means present at least in front of the viewer, which have a relief structure comprising optical pyramid-shaped elements for suggesting depth in images being viewed by distinguishing
10 between incident light on the left-hand eye and incident light on the right-hand eye of a viewer.

The present invention furthermore relates to an image display device suitable for use in the image display system according
15 to the invention.

Such a system is known from WO 98/17067. The system that is disclosed therein comprises an image display device or screen which displays images which have been position-shifted in
20 succession by image processing means. After being displayed on the screen, said images are converted by optical means disposed between the screen and the viewer. To that end, the optical means have a relief structure comprising elements of substantially pyramidal section. As a result of the presence
25 of the pyramids of the elements, whose apexes are directed towards the screen, a distinction is produced between incident light on a viewer's left-hand eye and incident light on said viewer's right-hand eye. This imparts a suggestion of depth in the images perceived by the viewer.

30 In practice it has become apparent that under certain circumstances the differences in clarity between the left-

hand eye and the right-hand eye that are created with the known system are not sufficient for imparting a sufficient perception of depth in the images being viewed.

- 5 Accordingly it is an object of the present invention to provide an image display system for improved display of images comprising depth information.

10 In order to accomplish that objective, the image display system according to the invention is characterized in that several pyramid-shaped elements are incorporated in the relief structure for each pixel of which the images are built up.

- 15 The advantage of the image display system according to the invention is the fact that the light output of the images formed by several pyramid-shaped elements has been increased. Not only does this make the obtained image clearer and easier to view, but it also appears to effect an improvement as
20 regards the perception of depth in the images being viewed.

In addition to that it is advantageous when using said several pyramid-shaped elements that the time-consuming, previously necessary alignment of the pyramids at the
25 position at which each pixel is displayed on the image display device is no longer critical as regards the obtained light output of the images and the desired depth effect. Thus, a significant saving as regards time and cost price in the manufacture of image display systems according to the
30 invention is obtained.

Another advantage is the fact that only one camera is

required at the recording or transmission end in order to effect the required depth perception at the receiving end. Furthermore, the perception of the suggested depth effect is not restricted to a limited area because the desired depth effect is substantially independent of the position of the viewer with respect to the image display device.

One embodiment of the image display system according to the invention is characterized in that the pyramid-shaped element are arranged in a matrix. As a result, a defined arrangement of rows and columns of successive pyramids is formed, which can easily be produced by means of a laser a technique, for example, and which can be inspected for possible faults in a simple manner, if necessary.

An embodiment of the image display system according to the invention which can be produced in a simple and quick manner is characterized in that the pyramid-shaped elements comprise four planes.

Another embodiment of the image display system according to the invention is characterized in that the pyramid-shaped elements each have a base, in which each base of the pyramids of a row takes up one position and each base of the pyramids of an adjacent row takes up a position complementary to said one position. The advantage of this position of the bases, which is different for each row, is that it leads to different perceptions by the left-hand eye and the right-hand eye of the active optical surface of one row in comparison with the other row. This contributes additionally to the difference in the clarity of perception of one eye in comparison with the other eye. As a result, the perception of

depth is enhanced.

One effect which further enhances the perception of depth is the following. It is a well-known fact in physiology that if
5 one eye receives more light than the other eye, the information relating to said greater amount of light will travel more quickly to the brains via the nerves as the amount of light being received increases. This leads to an additional difference in transit time or phase difference as
10 regards information travelling to the brains, which additional difference in transit time is interpreted by the brains as additional depth in the image being viewed.

Another embodiment of the image display system according to
15 the invention is characterized in that adjacent pyramid-shaped elements exhibit different distances/heights from the apex to the base of the pyramids.

By varying the height of the pyramids over the relief structure, an additional difference is obtained in that which
20 the two eyes perceive in the left-hand part and in the right-hand part of the image, respectively. This is in particular of importance with regard to the perception of depth in moving images, in which the movement of the image is converted into an additional difference between that which is
25 perceived by the left-hand eye and that which is perceived by the right-hand eye, as it were, so that the perception of depth is maintained.

In connection with said further embodiment it has moreover
30 become apparent that the image manipulation technique that may be used will remain simple and easy to implement in software, using common processors.

Another specific embodiment of the invention is characterized in that the height of the pyramids increases in one direction whereas said height decreases in the opposite direction.

The consequence of this is that movement of the image in a direction comprising a horizontal component, for example, will lead to the desired difference between the amount of light perceived by the left-hand eye and the amount of light perceived by the right-hand eye. This obtains both with regard to movement from the left to the right and with regard to movement from the right to the left. In both cases it will result in the desired perception of depth.

Yet another embodiment of the image display system according to the invention is characterized in that the direction of a row of the pyramid-shaped elements forming a matrix includes an angle of about 15 degrees with the horizontal.

With this embodiment of the image display system according to the invention it becomes possible to effect a difference between the amounts of light received by the left-hand eye and the right-hand eye, respectively, also if a movement in the image comprises a vertical component. As a result, depth can be perceived also in those cases where the direction of movement comprises a vertical component. Moreover, this embodiment reduces the extent of Moiré distortion, the well-known effect that occurs when block-shaped patterns are displayed on a television screen, for example, as a consequence of which moving lines are formed on the screen. The angle of 15 degrees has appeared to be an optimum angle in particular when equilateral pyramids are used and the angles of the base are 60 degrees, therefore, whilst a row begins with a base side which extends vertically.

One embodiment of the display device that is suitable for use in the image display system according to the invention is characterized in that the optical means, which have a relief structure comprising optical, pyramid-shaped elements, are in the form of a foil, a loose foil, if desired, to be applied to the display device, or in that the pyramid-shaped elements are integrated in the front plate of the display device.

Another advantageous embodiment of the image display system is according to the invention characterized in that the system comprises means for displaying an image built up of frames as well as image manipulation means, in which said image manipulation means are arranged for changing the clarity of frame pixels from the left to the right in one frame and changing the clarity of frame pixels from the right to the left in the other frame.

To the human eye, the effect achieved by means of the clarity-manipulated frames being displayed in succession is the same as the effect achieved by using neighbouring pyramids of different height. The image manipulation means, which are to be software-implemented, form an electronic alternative, as it were, for the hardware pyramids.

This embodiment presents an electronic alternative for the optical embodiment of the system, in which the height of neighbouring pyramids changes. The exchangeability between optical image processing and electronic image signal processing as regards the desired difference in light output between the left-hand eye and the right-hand eye is illustrated by this.

A further alternative embodiment of the image display system

is characterized in that the system comprises means which make it possible to control the extent to which the clarity from the left to the right and vice versa changes.

In this alternative embodiment it is possible to influence the extent to which a depth effect can be perceived in the images being displayed by controlling the degree/gradient of the clarity change.

One embodiment of the image display system which is also quite suitable for perceiving depth in images being displayed is according to the invention characterized in that the system comprises a chopper circuit connected to the display means, which circuit arranges for the frame clarity for pixels from one frame and from the other frame to be turned off alternately.

An improved embodiment of the image display system which is suitable for displaying stationary images is according to the invention further characterized in that said chopper circuit delivers a signal at a frequency which exhibits a frequency sweep.

One embodiment of the image display device which is suitable for use in the image display system is according to the invention characterized in that the optical means having a relief structure comprising optical pyramid-shaped elements consist of a foil to be arranged on the display device or are integrated in the front plate of the display device.

Given the fact that, in view of the above explanation, the position of the pyramids on the pixels is no longer critical, said foil may be an easily detachable foil; when such a foil is not used, the well-known image on the display device is

shown, whereas images imparting a perception of depth are shown when a foil which is easy to apply to the image display device is used.

5 The image display system according to the present invention will now be explained in more detail with reference to the appended drawing. In the drawing:

- Figure 1 shows part of the relief structure comprising optical pyramid-shaped elements for use in the image display system according to the invention;
 - 10 - Figures 2A, 2B and 2C are diagrams and a representation of a pyramid, respectively, which function to explain the system of Figure 1.
- 15 Figure 1 shows part of the relief structure which may be present on, for example, a secondary screen or on a display device, hereinafter called a screen, or be integrated therein. The relief structure may also be present on a foil, which may be detachable from the screen, if desired, or on a front plate of such a screen. Examples of a display device
- 20 are: a screen or monitor, for example for a television, whether or not provided with a cathode ray tube, an LCD screen or the like. The relief structure is made up of optical means in the form of optical, pyramid-shaped elements
- 25 1 present in front of the viewer, which have been formed in the foil by means of a fine laser technique, for example. The pyramids have a apex T directed away from a viewer who is looking at the screen. Upon exposure of the screen by a passing luminous spot, the pyramids 1, which are arranged in
- 30 a matrix formation in Figure 1, are exposed in succession on the side of their apexes, which light is refracted by the surfaces of the pyramids 1. In their simplest form, the

pyramids 1 of the illustrated pyramid-shaped elements
comprise four planes, including a base facing towards the
viewer. The luminous spot forms a pixel on a picture line in
a manner which is known per se, and several such lines form
5 an image. In those cases in which an image consists of two
"interlaced" frames or fields, the frames are written to the
screen as half-images. A pixel is made up of two pixels in
that case, one from a so-called uneven frame and one from an
even frame. The precise alignment of the various pixels on
10 the relief comprising pyramids 1, in a manner in which the
left-hand eye and the right-hand eye receive different
amounts of light from the pixels, so that the viewer can
perceive depth in the image on the screen, is problematic.
The way in which depth can be suggested in this way is
15 schematically indicated in Figure 1, in which the hatched
parts in the upper two pyramids 1 indicate the amount of
light which the left-hand eye, given the position of the
pyramids on the left-hand side, receives from the relief
structure, whilst the hatched parts in the lower two pyramids
20 1 indicate the amount of light which the right-hand eye
receives from the relief structure from the same left-hand
side. The differences in light or clarity with which the two
eyes have to cope and the associated differences between the
time of arrival of said clarity information at the brains and
25 the time of interpretation thereof impart the perception of
depth in the image being viewed.

Inaccurate alignment of the relief on the pixels will lead to
a poor perception of depth, however, and to the well-known
30 Moiré distortion in the image being viewed. The two problems
can be solved at once by incorporating several pyramid-shaped
elements 1 in the relief structure for each pixel of which

the images are built up. In this connection it may be considered to use a number of pyramids which ranges between 3 x 3 pyramids and (preferably) 9 x 9 or more pyramids per pixel, for example. Suitable techniques for realising the pyramids include: a laser technique, x-ray lithography, an I beam technique, or the mechanical super high precision diamond cutting, which currently is capable of realising up to 0.2 μm .

10 As Figure 1 furthermore shows, each base of the pyramid-shaped elements of the same - first - row extending to the right-hand bottom corner or to the right-hand upper corner takes up one position, in which the right hand tip of the base points to the right in all cases. Likewise, each base of
15 an adjacent - second - row extending to the right hand bottom corner or to the right-hand upper corner takes up a position complementary to said one position, in which the left-hand tip of the base points to the left. In this way a honeycomb structure of bases is formed, as it were, which leads to the
20 differences in clarity on which the perception of depth is based.

If a perception of depth is to be maintained in the case of moving images on the screen as well, the movement must be
25 converted into differences in clarity between the left-hand eye and the right hand eye, as it were, in order to create the perception of depth in this manner. This idea is embodied in a possible embodiment in which the successive pyramids 1 exhibit different distances/heights, measured from the apex T
30 to the base G of the pyramids. In particular, the height of the pyramids 1 increases from the left to the right in Figure 1, for example, whilst the height of the adjacent row of

pyramids 1 decreases from the right to left. The gradual difference in height increases from 0 to 10 μm , for example, for one row of pyramids and decreases from 10 to 0 μm for the adjacent row. If, for example, a vertical line portion of the image shifts in horizontal direction in that case, the differences in clarity resulting from the differences in height of the pyramids 1 will impart a perception of depth.

In order to achieve differences in clarity and perception of depth also in the case of the direction of movement comprising a vertical component, the relief structure as shown in Figure 1 is turned. In practice the optimum angle of turning is connected with the magnitude of the angles forming the base G of the pyramids 1. For the equilateral base comprising angles of 60 degrees, the direction of the row of the pyramid-shaped elements forming a matrix must extend at an angle of about 15 degrees to the horizontal, so that also vertical movements will impart perception of depth and the Moiré effect will be further suppressed. Thus, also movement of an object in the image from the rear to the front or vice versa can still be perceived as a realistic movement towards or away from the viewer.

Image displays systems which are known per se, such as television systems, are arranged for displaying images which, as mentioned above, are built up of even and uneven frames. Furthermore, the system may be fitted with image manipulation means which are arranged for changing the clarity of frame pixels from the left to the right in one frame and which are likewise arranged for changing the clarity of frame pixels from the right to the left in the other frame. It will be understood that it is possible to adjust the degree of depth

to be displayed by influencing the gradients of the clarity lines of Figures 2A and 2B, which is indicated by means of arrows. In practice the image displays system will comprise similar means for controlling the degree in which the clarity changes from the left to the right and vice versa. Reversal of the gradients of the clarity lines even makes it possible to display the image slightly in front of the screen, in which it seems as if the objects being shown emerge in part from the screen.

10

So far, it was movement in the image which led to a perception of depth. In order to further improve the perception of depth in the case of moving images, said perception can also be suggested by electronic means. This is done by incorporating a chopper circuit, which is connected to the display means, in the image display system, which chopper circuit arranges for the frame clarity for pixels from one frame and from the other frame being turned off alternately. This is shown more clearly in Figures 2A, 2B and 2C. In this case it obtains for the uneven frame that pixels present on the left on an uneven line will be displayed darker than pixels present on the right on the uneven line (see Figure 2A). Conversely it obtains that pixels present on the right on the even lines will be displayed darker than pixels present on the left on the even lines (see Figure 2B). This aspect makes it possible to contribute electronically rather than optically to the perception of depth, and also in this case a time difference is created between the reception of light by the left-hand eye and the right-hand eye. Figure 2C schematically shows how a matrix of pyramids 1 initially only receives light from the pixel of the even frame which, after refraction, is supplied to one of the eyes. Shortly

afterwards, the other eye receives the pixel from the uneven frame. The corresponding pixels have a different light intensity for the left-hand eye and the right-hand eye, however, thus enhancing the suggestion of depth perception in the images being displayed.

In the case of computer monitors, for example, the chopper frequency may be 10 MHz, depending on the number of pixels of the image. In particular in the case of stationary images, the perception of depth can be enhanced by having the chopper output signal exhibit a frequency sweep, which may be around 1 MHz in that case. The chopper signal having a varying frequency will produce an additional change in clarity in that case, which in turn will lead to an additional depth effect, in particular for stationary images.

The foregoing obtains both for "interlaced" image display, in which even and uneven frames are displayed in succession, and for "non-interlaced" image display. In the latter case the succession of frames is a succession of full frames rather than a succession of even and uneven frames, as was the case in the preceding explanation. The image display system can also be used on monitors and on game computers.

CLAIMS

1. An image display system comprising an image display
device and optical means present at least in front of
5 the viewer, which have a relief structure comprising
optical pyramid-shaped elements for suggesting depth in
images being viewed by distinguishing between incident
light on the left-hand eye and incident light on the
right-hand eye of a viewer, characterized in that
10 several pyramid-shaped elements are incorporated in the
relief structure for each pixel of which the images are
built up.
2. An image display system according to claim 1,
15 characterized in that the pyramid-shaped element are
arranged in a matrix.
3. An image display system according to claim 1 or 2,
characterized in that the pyramid-shaped elements
20 comprise four planes.
4. An image display system according to any one of the
claims 1 - 3, characterized in that the pyramid-shaped
elements each have a base, in which each base of the
25 pyramids of a row takes up one position and each base of
the pyramids of an adjacent row takes up a position
complementary to said one position.
5. An image display system according to any one of the
30 claims 1 - 4, characterized in that adjacent pyramid-
shaped elements exhibit different distances/heights from
the apex to the base of the pyramids.

6. An image display system according to claim 5,
characterized in that the height of the pyramids
increases in one direction whereas said height decreases
5 in the opposite direction.
7. An image display system according to any one of the
claims 1 - 6, characterized in that the direction of a
row of the pyramid-shaped elements forming a matrix
10 includes an angle of about 15 degrees with the
horizontal.
8. An image display system according to any one of the
claims 1 - 7, characterized in that the system comprises
15 means for displaying an image built up of frames as well
as image manipulation means, in which said image
manipulation means are arranged for changing the clarity
of frame pixels from the left to the right in one frame
and changing the clarity of frame pixels from the right
20 to the left in the other frame.
9. An image display system according to claim 8,
characterized in that the system comprises means which
make it possible to control the extent to which the
25 clarity from the left to the right and vice versa
changes.
10. An image display system according to claim 8 or 9,
characterized in that the system comprises a chopper
30 circuit connected to the display means, which circuit
arranges for the frame clarity for pixels from one frame
and from the other frame to be turned off alternately.

11. An image display system according to claim 10,
characterized in that said chopper circuit delivers a
signal at a frequency which exhibits a frequency sweep.

5

12. An image display device suitable for use in the image
display system according to any one of the claims 1 -
11, characterized in that the optical means, which have
a relief structure comprising optical, pyramid-shaped
elements are in the form of a foil to be applied to the
display device, or in that said optical means are
integrated in the front plate of the display device.

10




FIG. 1




FIG. 2A




FIG. 2B



FIG. 2C

INTERNATIONAL SEARCH REPORT

International Application No

PCT/NL 02/00629

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 G02B27/22

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G02B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data, INSPEC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 98 17067 A (WENGER KLAUS HERBERT GUENTER) 23 April 1998 (1998-04-23) cited in the application page 11, line 27 -page 13, line 21; figures 10,11	1
A	WO 01 04665 A (KOREA INST SCIENCE TECHNOLOGY ;LEE HYUN SOO (KR); SON JUNG YOUNG () 18 January 2001 (2001-01-18) page 6, line 21 -page 10, line 12; figures 3-6	1
A	US 5 083 199 A (BOERNER REINHARD) 21 January 1992 (1992-01-21) column 5, line 12 -column 8, line 4; figures 1,2	1

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the international search

31 October 2002

Date of mailing of the international search report

08/11/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Sarneel, A

INTERNATIONAL SEARCH REPORT

Inte Application No
PCT/NL 02/00629

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
WO 9817067	A	23-04-1998	NL	1004273 C1	20-04-1998
			NL	1006167 C2	01-12-1998
			WO	9817067 A1	23-04-1998
WO 0104665	A	18-01-2001	WO	0104665 A2	18-01-2001
US 5083199	A	21-01-1992	DE	3921061 A1	03-01-1991
			AT	122154 T	15-05-1995
			DE	59009001 D1	08-06-1995
			EP	0404289 A2	27-12-1990
			JP	2874966 B2	24-03-1999
			JP	3038633 A	19-02-1991

